




## Description

The SPC10 in SMT0-218 package provide the enhanced quality, easy manufacturing than typical through-hole TVS components. They can be connected in series and/or parallel to create various capability and flexible protection solutions.

## Functional Diagram




## Applications

- Communication Equipment
- Security & Protection
- Industrial Control Equipment
- Power Supply
- Automotive Electronics
- New Energy
- Lightning Protection


## Features

- Bi-directional
- Low clamping and slope resistance
- For automatic pick and place assembly and reflow process to reduce the manufacturing cost and increase the soldering quality compared to axial leads package
- Compact surface mount package design
- Meet MSL level 1, per J-STD-020, LF Maximum peak of 245 °C
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin (Sn)
- ESD follow IEC 61000-4-2
- Surge protection of lightning in accordance with IEC61000-4-5
- Halogen free and RoHS compliant
- Tube or tape and reel pack options available

## Package Outline Dimensions (SMTO-218)



Note: Coplanarity of solder side is controlled within 0.10 mm



Mounting Pad Layout (Inch)

Symbol	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	15.78	16.63	0.621	0.655
B	13.43	15.09	0.529	0.594
C	13.83	14.24	0.544	0.561
D	6.94	7.24	0.273	0.285
E	17.82	18.72	0.702	0.737
F	14.40	14.76	0.567	0.581
G	1.88	2.84	0.074	0.112
H	4.89	5.65	0.193	0.222
J	0.72	0.85	0.028	0.033

## Maximum Ratings and Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)

Parameter	Symbol	Value	Unit
Storage Temperature Range	$T_{STG}$	-55 to 150	°C
Operating Junction	$T_J$	-55 to 125	°C
Current Rating (8/20 $\mu$ s wave)	$I_{PP}$	10	kA


## Physical Specifications

Weight	Contact manufacturer
Case	Epoxy molding compound encapsulated
Terminal	Tin plated lead, solderability per MIL-STD-202 Method 208


## Environmental Specifications

Temperature Cycling	JESD22-A104
HTRB	JESD22-A108
MSL	JESDEC-J-STD-020, Level 1
H3TRB	JESD22-A101
RSH	JESD22-B106

## Part Numbering System




## Marking



**Electrical Characteristics** ( $T_A=25\text{ }^{\circ}\text{C}$  unless otherwise noted )

Part Number	Stand-off Voltage V <sub>R</sub>	Max. Reverse Leakage I <sub>R</sub> @V <sub>R</sub>	Breakdown Voltage V <sub>BR</sub> @I <sub>T</sub> Min Max		Test Current I <sub>T</sub>	Max. Clamping Voltage V <sub>CL</sub> @Peak Pulse Current (I <sub>PP</sub> )			Max. Temp Coefficient of V <sub>BR</sub>	Max. Capacitance 0 Bias 10KHz
			Min	Max		V <sub>CL</sub>	I <sub>PP</sub> (8/20 μs)	I <sub>PP</sub> (10/350 μs)		
							Min	Typical		
	(V)	(μA)	(V)	(mA)	(V)	(A)	(A)	(%/°C)	(nF)	
SPC10-030C	30	20	32	37	10	58	10000	1000	0.1	20
SPC10-058C	58	10	64	70	10	110	10000	1100	0.1	7.5
SPC10-066C	66	10	72	80	10	120	10000	1000	0.1	7.0
SPC10-076C	76	10	85	95	10	140	10000	1000	0.1	6.0
SPC10-086C	86	10	95	105	10	157	10000	1000	0.1	5.5

## I-V Curve Characteristics



## Performance Curve for Reference ( $T_A=25\text{ }^{\circ}\text{C}$ unless otherwise noted)




FIGURE 1 Peak Power Derating





FIGURE 2 Pulse Waveform

## Soldering Parameters




Reflowing Condition


Reflow Soldering Parameters		Lead-Free Assembly
Pre-heat	Temperature Min ( $T_{S(min)}$ )	150 °C
	Temperature Max ( $T_{S(max)}$ )	200 °C
	Time (min to max) ( $t_s$ )	60 ~ 120 seconds
Average Ramp Up Rate (Liquidus Temp ( $T_L$ ) to Peak		3 °C / second max.
$T_{S(max)}$ to $T_L$ Ramp-up Rate		3 °C / second max.
Reflow	Temperature ( $T_L$ ) (Liquidus)	217 °C
	Time (min to max) ( $t_L$ )	60 ~ 150 seconds
Peak Temperature ( $T_P$ )		245 <sup>+0/-5</sup> °C
Time of within 5 °C of Actual Peak Temperature ( $t_p$ )		20 ~ 40 seconds
Ramp-down Rate		6 °C / second max.
Time from 25 °C to Peak Temperature		8 Minutes max.
Do Not Exceed		245 °C

## Wave Soldering (Solder Dipping)

Peak Temperature	260 °C+0 /- 5 °C
Dipping Time	10 seconds
Soldering Number	1 time

Packaging Information

Tape		Symbol	Millimeters	Inches
		W	32 ± 0.3	1.260 ± 0.012
		E	1.75 ± 0.1	0.069 ± 0.004
		F	14.2 ± 0.1	0.559 ± 0.004
		D <sub>0</sub>	1.5 + 0.1 / 0.0	0.059 + 0.004 / -0.0
		P <sub>0</sub>	4.0 ± 0.1	0.102 ± 0.004
		P <sub>1</sub>	20.0 ± 0.1	0.787 ± 0.004
		P <sub>2</sub>	2.0 ± 0.1	0.079 ± 0.004
		A <sub>0</sub>	14.5 ± 0.1	0.571 ± 0.004
		B <sub>0</sub>	18.5 ± 0.1	0.728 ± 0.004
		T	0.40	0.016
		T <sub>1</sub>	7.8	0.029

Reel Size	Symbol	Inches	Millimeters
	D	Φ13.0	Φ330.0
	D <sub>1</sub>	Φ0.520±0.008	Φ13.2±0.2
	W <sub>1</sub>	1.417±0.079	36.0±2.0

Part Number	Weight (Typical)	Packaging Option	QTY' s
SPC10-XXXXC	4.33 g	Tape & Reel – 32 mm/13" tape	400 PCS

## Glossary

Item	Description
$V_C$	<b>Clamping Voltage</b> Voltage across TVS in a region of low differential resistance that serves to limit the voltage across the device terminals.
$V_R$	<b>Reverse Stand-off Voltage</b> Maximum voltage that can be applied to the TVS without operation. NOTE : It is also shown as $V_{WM}$ (maximum working voltage (maximum d.c. voltage)) and known as rated stand-off voltage ( $V_{so}$ ).
$I_R$	<b>Reverse Leakage Current</b> Current measured at $V_R$ . NOTE : Also shown as $I_D$ for stand-by current.
$V_{BR}$	<b>Breakdown Voltage</b> Voltage across TVS at a specified current $I_T$ in the breakdown region.
$I_{PPM}$	<b>Rated Random Recurring Peak Impulse Current</b> Maximum-rated value of random recurring peak impulse current that may be applied to a device.
$P_{M(AV)}$	<b>Rated Average Power Dissipation</b> Maximum-rated value of power dissipation resulting from all sources, including transients and standby current, averaged over a short period of time.
$P_{PPM}$	<b>Rated Random Recurring Peak Impulse Power Dissipation</b> Maximum-rated value of the product of rated random recurring peak impulse current ( $I_{PPM}$ ) multiplies by specified maximum clamping voltage ( $V_C$ ).
$C_J$	<b>Capacitance</b> Capacitance across the TVS measured at a specified frequency and voltage.
$V_{FS}$	<b>Peak Forward Surge Voltage</b> Peak voltage across an TVS for a specified forward surge current ( $I_{FS}$ ) and time duration. NOTE : Also shown as $V_F$ .
$I_{FS}$	<b>Forward Surge Current</b> Pulsed current through TVS in the forward conducting region. NOTE : Also shown as $I_F$ .
$\alpha_{V(BR)}$	<b>Temperature Coefficient of Breakdown Voltage</b> The change of breakdown voltage divided by the change of temperature.
$I_{PP}$	<b>Peak pulse Current</b> Peak pulse current value applied across the TVS to determine the clamping voltage $V_C$ for a specified wave shape.
$I_T$	<b>Pulsed D.C. Test Current</b> Test current for measurement of the breakdown voltage $V_{BR}$ . This is defined by the manufacturer and usually given in milliamperes with a pulse duration of less than 40 ms. NOTE : Also shown as $I_{BR}$ .

—(GB-T 18802.321 / IEC 61643-321 / JESD210A)





## ATTENTION

### Usage

1. TVS must be operated in the specified ambient temp.
2. Do not clean the TVS with strong polar solvent such as ketone, esters, benzene and halogenated hydrocarbon, to avoid damaging the encapsulating layer.
3. Please do not apply severe vibration, shock or pressure to TVS, to avoid element cracking.

### Replacement

1. If TVS is visually damaged, please replace it.
2. TVS is a non-repairable product. For safety sake, please use equivalent TVS for replacement.

### Storage

1. Storage Temp. Range: (-55 to 150) °C.
2. Do not store the TVS at the high temp., high humidity or corrosive gas environment, to avoid influencing the solder-ability of the lead wires. The product shall be used up within 1 year after receiving the goods.

### Environmental Conditions

1. TVS should not be exposed to the open air, nor direct sunshine.
2. TVS should avoid rain, water vapor or other condition of high temp. and high humidity.
3. TVS should avoid sand dust, salt mist, or other harmful gases.









### Max. Typical Capacitance of TVS

The typical capacitance of TVS is listed in the specifications. Designers may refer to it when designing TVS in High frequency circuit.

### Installation Mechanical Stress

1. Do not knock TVS when installing, to avoid mechanical damage.
2. Please do not apply severe vibration, shock or pressure to TVS, to avoid surface resin or element cracking.


Transient Voltage Suppressor ( Surface Mount ) Features Overview

Package Type	Series								
	DO-221AC					SMA6L			
	DO-214AA						SACB	SMBJ	P6SMB
	DO-214AB								
	DO-214AC			SMAJ	P4SMA	SMA6J			
	SOD-123FL	SMF	P4SMF						
	SMT0-218								
Product Outline (mm)									
									
									
									
									
									
									
									
									
$V_R / V_{WM} (V)$ Reverse Stand-off Voltage	5.0 ~ 250	5.0 ~ 85	5.0 ~ 440	5.8 ~ 468	5.0 ~ 250	5.0 ~ 50	5.0 ~ 440	5.8 ~ 512	
$P_{PPM} (W)$ (10/1000 $\mu s$ ) Rated Peak ImPulse Power Dissipation	200	400	600	500	600				
$I_{PPM} (kA)(8/20 \mu s)$ Rated Peak ImPulse Current									
Operating Temperature (°C)	-55 to +150								

Transient Voltage Suppressor ( Surface Mount ) Features Overview

Package Type										Series
	DO-221AC	○	○	○	○	○	○	○	○	
	DO-214AA	○	○	○	○	○	○	○	○	
	DO-214AB	SMCJ	1.5SMC	3.0SMCJ	SMDJ	5.0SMDJ	○	○	○	
	DO-214AC	○	○	○	○	○	○	○	○	
	SOD-123FL	○	○	○	○	○	○	○	○	
SMTO-218	○	○	○	○	○	SPC1	SPC3	SPC6	SPC10	
Product Outline (mm)										
$V_R / V_{WM} (V)$ Reverse Stand-off Voltage	5.0 ~ 440	5.8 ~ 512	5.0 ~ 440		12 ~ 170	380 / 430	66	58 ~ 76	58 ~ 86	
$P_{PPM} (W)$ (10/1000 $\mu s$ ) Rated Peak ImPulse Power Dissipation	1500		3000		5000	○				
$I_{PPM} (kA)$ (8/20 $\mu s$ ) Rated Peak ImPulse Current	○					1	3	6	10	
Operating Temperature ( °C )	-55 to +150					-55 to +125				

## Transient Voltage Suppressor ( Axial Lead ) Features Overview

Package Type	Series															
	DO-201				1.5KE	LCE										
	DO-41	P4KE														
	DO-15		SAC	P6KE												
	P600						5KP	15KPA	20KPA	30KPA						
Radial lead											SPCL1	SPCL3	SPCL6	SPCL10	SPCL15	SPCL20
Product Outline (mm)																
$V_R / V_{WM} (V)$ Reverse Stand-off Voltage	5.8 ~ 468	5.0 ~ 50	5.8 ~ 512	5.8 ~ 512	6.5 ~ 90	5.0 ~ 250	17 ~ 280	20 ~ 300	28 ~ 360	76	15 ~ 430	30 ~ 430	15 ~ 530	58 ~ 380	16 ~ 76	
$P_{PPM} (W)$ (10/1000 $\mu s$ ) Rated Peak ImPulse Power Dissipation	400	500	600	1500	5000	15000	20000	30000								
$I_{PPM} (kA)$ (8/20 $\mu s$ ) Rated Peak ImPulse Current											1	3	6	10	15	20
Operating Temperature (°C)					-55 to +150									-55 to +125		